COPYRIGHT 2004 ACS on STN

AN 102:63259 HCA

PRAI 1983JP-0033641

TI Polyolefin hot-melt adhesives

PA Sumitomo Chemical Co., Ltd., Japan

SO Jpn. Kokai Tokkyo Koho, 12 pp. CODEN: JKKKAF

DT Patent

LA Japanese

FAN.CNT 1

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
JP59159843	A2	19840910	1983JP-0033641	19830228
JP01007624	B4	19890209		
	JP59159843	JP59159843 A2	JP59159843 A2 19840910	JP59159843 A2 19840910 1983JP-0033641

19830228

AB A polyclefin hot-melt adhesive compn., exhibiting high adhesive strength at low temp., comprises (A) a polyclefin modified with unsatd. carboxylic acid or anhydride, or its blend contg. an unmodified polyclefin and (B) an ethylene-(meth)acrylic acid ester copolymer, optionally contg. a metal oxide, hydroxide, phosphate, carbonate, or carboxylate. Thus, a blend of 100 parts polyethylene grafted with 0.29% maleic anhydride (d. 0.957, melt index 2.2 g/10 min at 190.degree. and 2.16-kg load) and 10 parts 90.3:9.7 ethylene-Me methacrylate copolymer (I) [25101-13-7] (melt index 5.70 g/10 min) was kneaded at 180.degree. for 5 min, pressed to form a 0.3-mm sheet, sandwiched between steel plates preheated at 160.degree., and pressed for 1 s to give a laminate exhibiting 180.degree. peel strength 2.0 kg/cm, compared with 0 kg/cm for an adhesive no contg. I.

IT Adhesives

(hot-melt, carboxy-modified polyolefins contg. acrylic polymers, with high adhesive strength at low temp.)

IT 1309-42-8 1309-48-4, uses and miscellaneous 4067-14-5 7779-90-0 9002-88-4 9003-07-0 9010-79-1 9010-86-0 25101-13-7 25103-74-6 RL: USES (Uses)

(carboxy-modified polyolefin hot-melt adhesives contg., with high adhesive strength at low temp.)

IT 9006-26-2 25722-45-6 31069-12-2 93060-02-7

RL: USES (Uses)

(graft, hot-melt adhesives contg., with high adhesive strength at low temp.)

IT 9010-77-9

RL: USES (Uses)

(hot-melt adhesives contg., with high adhesive strength at low temp.)

TT 7429-90-5, uses and miscellaneous 12597-69-2, uses and miscellaneous 24937-78-8 25038-54-4, uses and miscellaneous 25067-34-9

RL: USES (Uses)

(sheets, hot-melt adhesives for, carboxy-modified polyolefin hot-melt adhesives for, with high adhesive strength at low temp.)